



D210 Wireless Payment Terminal

PAX's D210 is a revolutionary payment device designed to interact with customers. Supporting Bluetooth, Wi-Fi, GPRS or cable connection, the D210 connects to a wide range of existing and new smart devices to keep up with an emerging marketplace. Apple Inc. has given the D210 a special certification called MFi meaning that Apple has tested and approved the D210 to meet the highest performance standards for integration with any iPad or iPhone.

Made for
 iPod  iPhone  iPad

Ensuring transactional security with PCI PTS 3.x certification, the D210 streamlines payment into a unique personal program, and you can now take all your value-added applications on the D210 to provide a high-tech and user-friendly customer interaction.

D210 Wireless Payment Terminal

FEATURES & BENEFITS



High Reliability & Exceptional Performance

- Smart card, magstripe & contactless enabled
- Stylishly designed for comfort and convenience
- Contactless card reader supporting NFC
- 2.4 inch colour screen
- Large memory capacity

Perfect Expansibility

- Open and flexible OS for customized value-added services
- USB port for high-speed data transmission
- Supports Bluetooth, Wi-Fi, GPRS and cable

Unprecedented Security

- PCI PTS 3.x approved
- Secure embedded area for keys

SPECIFICATIONS

Processor

32-bit secure processor

Memory

64MB (32MB Flash, 32MB SDRAM)

Display

2.4 inch TFT LCD

Printer

Thermal printer, speed: 18 lines per second
Paper roll width / diameter: 58mm / 38mm

Keypad

10 numeric keys, 5 function keys

Magnetic card reader

Track1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader

MasterCard PayPass & Visa payWave
13.56MHz, ISO / IEC 14443 Type A / B,
Mifare®, Felica, NFC

Communication

Wi-Fi / Bluetooth / GPRS

Card slots

2 SAMs
or 1 SAM, 1 SIM

Peripheral Ports

1 x Multi-Single mini HDMI port

Security

PCI PTS 3.x certified

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

Voltage

Input: 100 - 240V AC, 50 / 60 Hz, 0.8A
Output: 12VDC, 2A

Battery

Li-Ion battery 1300mAh, 3.7V

Physical

Length: 162.5mm
Width: 82.5mm
Height: 56.5mm

Weight

365g with battery

Accessories

Adapter & base

Certifications

PCI PTS 3.x
EMV L1 & L2
MasterCard PayPass
Visa payWave
EMV Contactless L1

